



## The Sullair 260 Portable Air Compressor

260 cfm at 100 psig ■ 7.4 m<sup>3</sup>/min at 7 bar

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- Wheel bearing grease fittings
- Large tool box compartment
- Curbside instrument panel
- Protective shutdown switches
- SSAM – Shutdown System and Annunciation Module
- Idle warm-up valve
- Rocker type start switch
- Fuel/Water separator
- Two-stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Galvanneal sheet metal
- Durable powder coat finish
- Wide track
- Recessed tail lights
- Rear bumper

  
**SULLAIR**<sup>®</sup>  
*Always air. Always there.™*



**Curbside Instrument Panel Featuring SSAM**  
Shutdown System & Annunciation Module.



**Wheel Bearing Grease Fitting**  
Offers convenient wheel bearing lubrication thru zerk fittings.



**Rotary Screw Design**  
by Sullair, the pioneer in rotary screw technology.



**Sullair AWF Compressor Fluid**  
Improved hot and cold weather lubrication. Longer compressor fluid life. Extended air end warranty.

**Designed for Total Accessibility and Reliability**

**Rotary Screw Compressor**

**Ample Service Doors**

- Large service doors provide access to fuel tank, engine, compressor and tool compartment
- Service doors feature non-rusting hinges, with built-in weather strip and stainless steel T-type door retainers
- Rear service panel provides access to side by side compressor fluid cooler and engine radiator
- Serviceable components within easy reach
- Routine maintenance is simplified
- Reduced downtime and service cost

**Modular Canopy and Frame**

- Canopy easily removed in one piece for major service
- Modular design reduces replacement costs
- Exposed, single point lifting bail

**0 to 100% Capacity Control**

- Pneumatic inlet valve and unloaded starting

**Highway Towable Running Gear**

- 3" square drawbar
- Adjustable height hitch (14", 16", 18")
- Quick-change hitch
- Screw jack with pad
- Transport security chains
- Heavy duty leaf spring suspension
- Wide track stability

**Large Curbside Tool Box**

**Curbside Instrument Panel**

- Hinged, padlockable cover
- Mechanical air pressure gauge and hourmeter
- Rocker type engine start switch
- Idle warm-up switch

**SSAM—Shutdown System & Annunciation Module**

- Shutdown with annunciator light for high compressor temperature, high engine coolant temperature, low engine oil pressure and engine under-speed

**Durable, Baked-on Powder Coat Finish**

**Two-Stage Dry Type Air Filters**

- Separate filters for engine and compressor

**Tier 4 Interim / Stage III B Emissions Compliant Engines\***

**Air End Warranty**

- 2-year standard warranty
- 5-year or 10,000-hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters

**Quiet Operation**

- Meets US EPA sound requirements of 76 dBA @ 7 meters

\* CAT only.

**Customize the compressor to meet your specific requirements with Sullair's options**

- Special paint
- Hose reels, single and dual
- Spark arrestor
- Fuel level gauge
- Gauge package

- Tachometer
- Brakes (recommended where required by law)
- Mechanical parking brakes
- Block heater

- Ball hitch
- Air filter maintenance indicators
- Air filter safety elements
- Low fuel shutdown

**SPECIFICATIONS, WEIGHTS AND DIMENSIONS—SULLAIR 260 PORTABLE COMPRESSOR**

Delivery @ Rated Pressure	Rated Pressure psig bar	Pressure Range psig bar	Designated Model	Weight **		Length (drawbar)		Length (canopy)		Width		Height		Track Width		Tire Size (load range)				
				lbs	kg	in	mm	in	mm	in	mm	in	mm	in	mm					
260 acfm 123 l/s 7.4 m³/min	100	7	80-125	5.5-8.5	2-Wheel	2840	1288	2595	1177	143.3	3640	85.1	2162	65.4	1661	59.9	1522	55	1397	205/75D15
						Less Running Gear	2585	1173	2340	1061	-	-	85.1	2162	47.5	1207	49.0	1245	-	-

Engine Make	Engine Type	Engine Model	Displacement		Cylinders	Bore and Stroke		Rated Speed	Rated Power	
			in³	cc		in	mm	rpm	hp	kW
Caterpillar	Diesel	C3.4 (Tier 4 Interim)	201	3272	4	3.70 x 4.72	94 x 120	2500	74	56
John Deere	Diesel	5030TF270 (Tier 2)	186	3028	4	3.39 x 4.13	86 x 105	2500	82	61

John Deere model available outside North America and the EU Countries

Capacity per CAGI/PNEUROP PN2CPTC3. (Annex D to ISO 1217)

\*\* Weights are for John Deere. For Caterpillar, deduct 80 lbs (37 kg).



**Sullair**  
3700 East Michigan Boulevard  
Michigan City, IN 46360  
Telephone: 219-879-5451  
[www.sullair.com](http://www.sullair.com)

© Copyright 2013 Sullair. All rights reserved.  
The color green is a registered trademark of Sullair.  
Specifications subject to change without notice.  
SSL-1148EN 1404R

