

**STANDARD EQUIPMENT**

ISO Standard cabin
All-weather steel cab with 360° visibility
Safety glass windows
Rise-up type windshield wiper
Sliding fold-in front window
Sliding side window(LH)
Lockable door
Hot & cool box
Storage compartment & Ashtray
Radio & USB player
Cabin roof-steel cover
12 volt power outlet (24V DC to 12V DC converter)
Computer aided power optimization (New CAPO) system
3-power mode, 2-work mode, User mode
Auto deceleration & one-touch deceleration system
Auto warm-up system
Auto overheat prevention system
Automatic climate control
Air conditioner & heater
Defroster
Self-diagnostics system
Starting Aid (air grid heater) for cold weather
Centralized monitoring
LCD display
Engine speed or Trip meter/Accel.
Clock
Gauges
Fuel level gauge
Engine coolant temperature gauge
Hyd. oil temperature gauge
Warnings
Overload
Communication error
Low battery
Air cleaner clogging
Indicators
Max power
Low speed/High speed
Fuel warmer
Auto idle
Door and cab locks, one key
Two outside rearview mirrors
Fully adjustable suspension seat with seat belt
Pilot-operated slidable joystick
Four front working lights
Electric horn
Batteries (2 x 12V x 100 AH)
Battery master switch
Removable clean-out dust net for cooler
Automatic swing brake
Removable reservoir tank
Fuel pre-filter
Boom holding system
Arm holding system
Track shoes (600mm, 24")
Track rail guard
Accumulator for lowering work equipment
Electric transducer
Lower frame under cover (Normal)

**OPTIONAL EQUIPMENT**

Fuel filler pump (35 L/min)
Beacon lamp
Single-acting piping kit (breaker, etc.)
Double-acting piping kit (clamshell, etc.)
Quick coupler
Travel alarm
Booms
5.68 m, 18' 8"
8.2 m, 26' 11" Long reach
Arms
2.0 m, 6' 7"
2.4 m, 7' 10"
2.92 m, 9' 7"
3.9 m, 12' 10"
6.3 m, 20' 8" Long reach
Climate control
Air conditioner only
Heater only
Cabin FOPS/FOG (ISO/DIS 10262)
FOPS (Falling Object Protective Structure)
FOG (Falling Object Guard)
Cabin lights
Cabin front window rain guard
Sun visor
Track shoes
Triple grousers shoe (700 mm, 28")
Triple grousers shoe (800 mm, 32")
Triple grousers shoe (900 mm, 36")
Double grousers shoe (710 mm, 28")
Full track rail guard
Lower frame under cover (Additional)
Pre-heating system, coolant
Tool kit
Operator suit
Rearview camera
Seat
Mechanical suspension seat with heater
Hi-mate (Remote Management System)
Fuel warmer
Viscous fan clutch

We build a better future

**Robex**  
**220LC-9S**  
**220LC-9SH**  
 With Tier 2 Engine installed



Standard and optional equipment may vary. Contact your Hyundai dealer for more information. The machine may vary according to International standards. All imperial measurements rounded off to the nearest pound or inch.

**PLEASE CONTACT**

www.hyundai-ce.com

2011.07 Rev. 0

**HYUNDAI**  
 HEAVY INDUSTRIES CO.,LTD.  
**CONSTRUCTION EQUIPMENT**

Head Office (Sales Office)  
 1, JEONHA-DONG, DOONG-GU, ULSAN, KOREA. TEL: (82) 52-202-7970, 7726, (9971) FAX: (82) 52-202-7979, 7720

Americas Operation: Hyundai Construction Equipment Americas, Inc.  
 955 ESTES AVENUE, ELK GROVE VILLAGE, IL, 60007, U.S.A. TEL: (1) 847-437-3333 FAX: (1) 847-437-3574

Europe Operation: Hyundai Heavy Industries Europe N.V.  
 VOSSENDAAL 11, 2040 GEEL, BELGIUM. TEL: (32) 14-56-2200 FAX: (32) 14-59-3405

India Operation: Hyundai Construction Equipment India Pvt., Ltd.  
 PLOT NO-A-2, CHAKAN INDUSTRIAL AREA, VIL - KHALUMBRE, TALUK - KHED., DIST - PUNE 410 501, INDIA  
 TEL: (91) 21-3530-1700 FAX: (91) 21-3530-1712

**HYUNDAI**  
 HEAVY INDUSTRIES CO.,LTD.

